

FIS-L series Stone-buriers standard features: separation grill and rear leveling bonnet; reverse blade rotation; 300mm/12 in. diameter cage roller; maximum working depth 15 cm/ 6 in.; lateral chain transmission; 540 rpm; PTO with friction disk; manual depth regulation (lateral); single-speed gearbox (230 rpm); 4 curved blades/flange; 2 spare blades with screws; CAT. 1 hitch adjusts laterally

	<u>WORKING</u> <u>WIDTH (in.)</u>	<u>BASE</u> <u>WEIGHT</u> <u>(lbs)</u>	<u>NUMBER</u> <u>FLANGES</u>	<u>NUMBER</u> <u>BLADES</u>
FIS-L Models for tractors up to 50 HP:				
FIS-L .80 (HP 25-35)	31	572	4	16
FIS-L 1.00 (HP 25-35)	39	638	6	24
FIS-L 1.30 (HP 25-35)	51	726	7	28
FIS-L 1.45 (HP 25-50)	57	770	8	32
FIS-L 1.65 (HP 25-50)	64	836	9	36

**FIS-L Options & Accessories:**

- Hydraulic depth regulation (2 cyl.w/blocking valve)
- PTO with automatic limiter
- Packer Roller with Reinforced Mounting
- Blades (cod.0027Z) 60x 7 (curved or squared)

**MELO SEEDERS (drop seeder, mount included)**

- FIS-L .80 (HP 25-35)
- FIS-L 1.00 (HP 25-35)
- FIS-L 1.30 (HP 25-35)
- FIS-L 1.45 (HP 25-50)
- FIS-L 1.65 (HP 25-50)